



**SPECIFICATIONS:**

1. CONTACT RESISTANCE: 20m OHM MAX.
2. INSULATION RESISTANCE: 300M OHM MIN. AT DC 500V.
3. VOLTAGE WITHSTANDING: AC 1000V FOR ONE MINUTE.
4. INSERTION FORCE: 4.0KG MAX.
5. WITHDRAWAL FORCE: 1 - 3.5KG.
6. CURRENT RATING: 2A

5	RIVET	1	AL	NICKEL PLATED	
4	CONTACT TERHINAL	4-8	BRASS 0.7t	Cu10%, Sn90%	
3	EARTH TERMINAL	1	PBSR-H 0.25t	Cu10%, Sn90%	
2	INSULATOR	1	P.B.T.	VALOX 420-SED	UL94V-0
1	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

ARRANGEMENT OF CONTACTS					
NO OF CONTACTS	4	5	6	7	8
MODEL NO	DNS4F01K00E	DNS5F01K00E	DNS6F01K00E	DNS7F01K00E	DNS8F01K00E

<b>PANSTRONG COMPANY LTD.</b>		DRAWN BY		<b>TOMMY</b>	
		CHECKED			
TITLE:		<b>4-8PIN DIN SOCKET</b>		APPROVED	
PART NO:		<b>DNS*F01K00E</b>		DRAW NO	
DRAW. BOX NO:					
SCALE		REV	<b>A</b>	UNIT	<b>mm</b>